



Temperature & Pressure Data Logger EBI 12

for process validation in the VH₂O₂ sterilizer

RED LINE

EBI 12-TP290

The EBI 12 data logger was developed for the high-precision measurement of a fine vacuum. It is used to measure the absolute pressure in the VH₂O₂ sterilizer.

- High accurate pressure measurement
- High accurate temperature measurement up to 0.1 °C
- External temperature probe, Ø1.95 mm, rigid, axial

Technical Data:

Operating Temperature	0 °C ... +85 °C
Measuring range: Temperature	0 °C ... +85 °C
Measuring range: Pressure	0.1 ... 1,050 mbar (0.1 ... 788 Torr)
Accuracy: Temperature	± 0.1 °C
Accuracy: Pressure	± 0.25 mbar (0.1 mbar ... 50 mbar) ± 5% from the measurement (50 mbar ... 100 mbar) ± 1% FS (100 mbar ... 1,050 mbar)
Resolution: Temperature	0.01 °C
Resolution: Pressure	0.1 mbar
Data memory	2x 33,440 measurements
Sensor: Temperature	PT1000, class A
Sensor: Pressure	Piezoresistive pressure sensor
Measurement interval	250 ms ... 24 hours
Real-time data transmission	Yes
Storage Temperature	-20 °C ... +70 °C
Measurement modes	<ul style="list-style-type: none"> • endless measurement • Measure upon starttime • Start immediately until end of memory • Start- / Stop measurement
Battery	Lithium, 3.6 V, User-replaceable
Dimensions	(Ø x H) 48 mm x 35 mm
Weight	app. 90 g
Housing Material	316 L stainless steel / PEEK
Protection class	IP68
Factory Calibration Certificate	0 °C and +60 ° ≤ 0.5 mbar and 50 mbar (at +25 °C) ≤ 0.5 mbar, 10 mbar and 50 mbar (at +60 °C)



Standards and Directives:

- 2014/53/EU
Radio Equipment Directive RED

Type	Description	Part-No
EBI 12-TP290	L = 40 mm	1340-6666

Xylem Analytics Germany Sales GmbH & Co.KG, ebro -Peringerstr. 10 – D-85055 Ingolstadt, Germany
Tel +49 841 954780 – Fax +49 841 95478-80

Website: www.ebro.com – E-Mail: ebro@xylem.com

ebro® is a registered trademark of Xylem Inc. or one of its subsidiaries. Technical changes reserved.
© 2014 Xylem Analytics Germany Sales GmbH & Co. KG.

May 2022

-ebro-
a xylem brand